

TECHNICAL SPECIFICATION

NEO- 3.3KWDCS



Input Characteristics

Voltage	: 110VAC-300VAC, 230VAC Nominal Voltage
Current	: <32A @110VAC with full load <16A @200VAC with full load <14A @230VAC with full load <10A @300VAC with full load
Inrush Current	: <40A
Frequency	: 47-53HZ

Protections

Over Current Protection	: 25A +/- 0.5A
Input & Output Over Voltage Protection	: Provided
Input & Output Under Voltage Protection	: Provided
Over Temperature Protection	: 65° C
Battery Reverse Connection Protection	: Provided
Output Short Circuit Protection	: Provided
Shoot Through Fault Protection with Recovery :	Charger will shutdown automatically and charger will re-start after removing fault
Ground Fault Protection	: Provided
Load Balance	: Provided

Indicators

LCD Display	: Charging Percentage, Voltage and Current, Ready to charge ,Fault indication
Mains ON Indicator	: Red LED
Charging Indicator	: Green Blinking
Charge Complete	: Green Constant
Battery Compatibility	: Lithium-Ion

Output Characteristics

Voltage	: 60V +/- 0.2V DC Each Output
Current	: 25A Each output
Efficiency	: >90%
Ripple	: <1000mV
Noise	: <2000mV

Features

Multiple Charging Points	: Provided
Billing System	: Provided
Standard	: IP54

Environmental Conditions

Operating Temperature	: 0-55° C
Storage Temperature	: 0-70° C
Humidity	: 75 RH +/-5%

Mechanical

Dimensions	: 350*450*140 (in mm)
Weight	: ~ 16Kg
Enclosure	: MS
AC Input Connector	: 3-core, 8sq.mm cable with standard connector
DC Output Connector	: 2-Core, 2.5sq.mm cable with SB50 Connector each output

NEOTREND EV SYSTEMS PVT LTD

3rd Floor, Block 3A, Udai Square, Phase-V, IDA, Cherlapally, Hyderabad-500051, Telangana, India.

🌐 www.neotrendev.com ✉ info@neotrendev.com